

**SITEPROTECT Fire Call Point Alarm**

Part Number: CYG2

Fire Call Point Alarm

The SITEPROTECT fire call point alarm operates using a single battery pack and can be used externally.

This radio alarm device has also been designed as a standalone alarm unit. These devices are normally situated around a site in prominent places on main escape routes, stairwells and on, or near fire points where they are visible in case of an emergency.

This alarm has a 110-decibel sounder and an LED beacon for visual alerts. The call point is resettable and can be programmed with a sounder delay.

Activating a call point will result in a site wide alert.



Technical Specification	CYG2
Size H x W x D (mm)	265 x 170 x 90
Battery Life	12 Months
Aerial Height (mm)	230
Weight (KG [lbs.])	1.72 [3.80]
IP Rating	IP65
Frequency	868 MHz
Receiver Category	Category 1
Sound Pressure (dBA @ 1ft.) *	110
Power	See table below
Aerial Type	External Mount
Warranty	12 Months
Relative Humidity	> 95% to 25°C
Operative Temperature	-10°C to + 55°C
Storage Temperature	-10°C to + 55°C

Other devices in the range

Part Number	Product Description
CYG1	SITEPROTECT Control Panel
CYG2	SITEPROTECT Fire Call Point Alarm
CYG2PIR	SITEPROTECT Fire Call Point Alarm with PIR
CYG2F	SITEPROTECT Fire Call Point and First Aid Alarm
CYG2FPIR	SITEPROTECT Fire Call Point and First Aid Alarm with PIR
CYG2/85DB	SITEPROTECT Fire Call Point Alarm 85 Decibel
CYG5	SITEPROTECT First Aid Alert Point
CYG5PIR	SITEPROTECT First Aid Alert Point with PIR
CYG3L	SITEPROTECT Heat Detector
CYG3LPIR	SITEPROTECT Heat Detector with PIR
CYG4L	SITEPROTECT Smoke Detector
CYG4LPIR	SITEPROTECT Smoke Detector with PIR
CYGRU	SITEPROTECT Repeater Unit
CYGLDAP02	SITEPROTECT Lockdown Alarm Panel
CYGLDA01	SITEPROTECT Lockdown Alarm